



MURIATE OF POTASH
Specialty Coarse Grade
0-0-60

<u>CHEMICAL ANALYSIS</u>	<u>MIN</u>	<u>MAX</u>	<u>TYPICAL</u>
TOTAL POTASH (wt. %K ₂ O)	60.0		60.6
CHLORIDE (wt. %Cl)	47.0		47.7
POTASSIUM (wt. %K)			50.3
SODIUM (wt. %Na)			1.35
CALCIUM (wt. %Ca)			0.03
MAGNESIUM (wt. %Mg)			0.03
BROMINE (wt. %Br)			0.01
SULFATE (wt. %S ₀₄)			0.05
TOTAL ORGANICS (wt. %)			0.20
TOTAL WATER INSOLUBLE (wt. %)			0.4
MOISTURE (wt. %H ₂ O)			0.02
pH of 10% wt./wt. AQUEOUS SOLUTION			9
PRODUCT CONDITIONER (ppm Amine)			150

PHYSICAL ANALYSIS

COLOR			Brick Red
ANGLE OF REPOSE (Degrees)			33
BULK DENSITY (kg per m ³ /lbs per ft ³)			
• LOOSE			1000/62
• TAPPED			1125/70
SIZE GUIDE NUMBER (SGN)	200	220	210
UNIFORMITY INDEX			56
SCREEN ANALYSIS (% By Weight)			
<u>Tyler</u>			
+6	0	0	0
+8	7	13	10
+14	97	99	98

Please obtain a Material Safety Data Sheet for more information.

To the best of the Manufacturer's knowledge and belief the information contained herein is accurate and reliable as of the date compiled. However, the Manufacturer makes no representation, warranty or guarantee as to the information's accuracy, reliability, completeness or timeliness. It is the user's responsibility to determine the suitability and completeness of such information for the user's own particular use or purposes. The Manufacturer does not accept any liability for any loss or damage that may occur from any use of this information.

AGRIUM, 13131 Lake Fraser Drive SE, Calgary, Alberta T2J 7E8; Phone: (403) 225-7000.

Agrium U.S. Inc., 4582 S. Ulster Street, Suite 1700, Denver, Colorado 80237; Phone: (303) 804-4400.